

## **Traffic Speed Flow Model For The Mix Traffic On Vadodara Arterial Road**

Krishn Rathod<sup>1</sup>, Jayesh Juremalani<sup>2</sup>, Suresh Damodariya<sup>3</sup>

<sup>1</sup> M.Tech. Student, Civil Department, Parul Institute of Engg. & Tech., Vadodara, Gujarat, India

<sup>2</sup> Asst. Professor, Civil Department, Parul Institute of Engg. & Tech., Vadodara, Gujarat, India

<sup>3</sup> Reader, Civil Department, Parul Institute of Engg. & Tech., Vadodara, Gujarat, India

**Abstract—** *The traffic in mixed flow can be classified as fast moving and slow moving vehicles or motorized and non motorized vehicles in India. The vehicle also deviate in size manoeuvrability, control, static and dynamic characteristics.*

*The effect of curve on speed under the mix traffic condition is carried out in present study. Thus, the purpose of this study is to calculate the capacity of the urban arterial roads. The study and research consists of analyzing the arterial Vadodara roads which are divided in four lanes. A part for straight stretch, curve stretch also selected to study the reduction of the speed. By considering the straight road section, the speed flow model is developed.*

**Keywords—** *Urban Roads, Mixed traffic, Straight Section, Curve Section, Speed Flow Model.*

### **I. INTRODUCTION**

Urbanization – The population shift from rural to urban areas, “The gradual increase in the proportion of people living in urban areas”, which causes the travel patterns to be very complex. To investigate the operational characteristics of the mixed traffic flow consisting of different vehicles (large vehicles, cars and bicycles) and it is governed by different factors like side friction, composition present of non-motorized transport, the curvature of the roads, variation in volume, density and velocity etc.

Thus, the purpose of this study is to calculate the capacity of the urban arterial roads. The study and research consists of analyzing the arterial Vadodara roads which are divided in four lanes. A part for straight stretch, curve stretch also selected to study the reduction of the speed.

Here, the variation in speeds will be observed and the variation in curved portion compared to the straight portion will be noted. The classical speed flow relation for straight and curve has been carried out.

**Video graphic technique** is used to capture the data for four lane divided roads. It will be carried out between 7 AM to 9 PM. The capacity base on speed flow was determined for straight portion. The spot speed method is used to capture video graphics analysis on big screen and volume vehicle per hour and speed kmph and also time means speed converted in to space means speed to established speed, flow relationships.

Heterogeneous traffic composition is comprised by most of the Indian cities today. Metropolitan cities contain two wheelers and four wheelers excessively making them the maximum running vehicles today. The presence of vehicles of wide ranging static and dynamic characteristics defines the existing heterogeneous traffic on urban roads of developing countries like India. The unhampered movement of the vehicles which are running on road space is responsible for the lane concept and expression of flow values, based on standard lane width.

As a result, different types of vehicles share the same road space without any physical separation. Thus Vadodara city becomes the appropriate site for the study of the arterial roads because the urban arterial divided roads are the important traffic corridors as they carry high volume of traffic without lane discipline and separation.

Traffic flow become more complicated because of absence of hierarchical functioning of different categories of arterial road in metropolitan cities like Vadodara.

The study at present is aimed to get the case study of limited traffic flow characteristic of excess control urban arterials road for that fastest growing of Vadodara city. As mentioned above, this study is carried on urban arterial road in Vadodara city. Video Graphic Survey is used to carry classified volume count for 16 hours on arterial road. Also, Video graphic survey is carried out for spot speed study. This also means that the PCU factor microscopic traffic characteristics are out of the scope.

## II. METHODS AND MATERIAL

### A. Objectives

- 1) Analysis and study of the speed characteristic of arterial road.
- 2) Evaluation of the effect of curve on speed.
- 3) Study of speed flow relationship of arterial roads.

### B. Literature Review

**B. r. marwah & Bhuvnesh Singh (2004):** Have study LOS classification evolved in this study will be helpful to identify deficiencies of an urban road system and to plan for alternate improvement measures to attain a desired level of service. The study of the simulation results during analysis clearly demonstrates the capability of model simulate urban heterogeneous traffic flow condition.

**Kazushi SANO, Chu Cong MINH, Chu Cong MINH (2005):** The purpose of this study addresses a comprehensive analysis of motorcycle behavior and operation through videotaping of some roads that have significant motorcycle proportion. Statistical analyses of the empirical data were utilized to demonstrate the characteristics of motorcycle speed, time headway regarding to traffic flow. The present paper provides a basic understanding of characteristics of motorcycle traffic. The finding obtains from this research may be used to develop new procedures for Highway Capacity Manual (HCM), which adapt developing countries as well as provide the data needed to develop a motorcycle simulation model.

**Partha Pratim Dey, Satish Chandra and Gangopadhaya (2006):** Have study that Most of the studies in the literature indicate that speed on a highway flow the normal distribution. The present study indicates that the speed distribution may be unimodal or a bimodal curve depending upon the variation in the speed of different categories of vehicles moving on the highway. The mathematical equation are suggest for unimodal and bimodal speed distribution curves, and their parameter evaluated at 17 different section two lane roads in India. It is observed that the proportion of slow moving vehicles is not a true indication of bimodality in the speed data. The spread ratio define as the ratio of difference between 85<sup>th</sup> percentile and mean speed to the difference in mean stream speed and 15<sup>th</sup> percentile speed, is better correlated with the shape of the distribution curves. The speed follows the unimodal curve only when the spread ratio is in the range of 0.69-1.35.

**Jorge A. Laval and Carlos F. Daganzo (2006):** Have studied that it is postulated that lane-changing vehicles create voids in traffic streams and that these voids reduce flow. This mechanism is described with a model that tracks lane changers precisely, as particles able with realistic mechanical properties. The model has four easy-to-measure parameters and reproduces without re-calibration two bottleneck phenomena previously thought to be unrelated: (i) the drop in the discharge rate of freeway bottlenecks when congestion begins, and (ii) The relation between the speed of a moving bottleneck and its capacity.

**Arasan VT (2008):** Has studied the effect of traffic volume and road width on PCU values under Indian traffic conditions by using microscopic simulation technique. Authors have dealt with (a) impedance caused to traffic flow by the different categories of vehicles and (b) to study the effect of road width on PCUs of vehicles. Conclusions drawn by the study states that (i) PCUs of a vehicle significantly changes with change in traffic volume, (ii) PCUs values of any vehicle type increases with the increase in the width of road space, (iii) PCUs value of a vehicle type is a dynamic quantity and not a constant and (iv) PCUs value of vehicle type is dependent upon the percentage of that vehicle type in total traffic mix.

**Sven M. and Moor Bart D. (2008):** They explained that scientific field of traffic engineering encompasses a rich set of mathematical techniques, as well as different backgrounds. The paper provides an overview of what is currently the state of the art with respect to traffic flow theory. Starting with a brief history, they introduced the microscopic and macroscopic characteristics of vehicular traffic flows and some performance indicators that allow assessing the quality of traffic operations.

**Hemang chaudhari (2010):** Have study the Lane choice behavior. To develop dynamic vehicle equivalent factors for heterogeneous traffic on arterial road. Case study Lucknow and Chandigarh city.

**Xiangjie Kong, Guojiang Shen , Feng Xia, and Chuang Lin (2011):** Have study presents a new two-direction green wave intelligent control strategy to solve the coordination control problem of urban arterial traffic. The whole control structure includes two layers the coordination layer and the control layer. Public cycle time, splits, inbound offset and outbound offset are calculated in the coordination layer. Public cycle time is adjusted by Fuzzy Neural Networks (FNN) according to the traffic flow saturation degree of the key intersection. Splits are calculated based on historical and real-

time traffic information. Offsets are calculated by the real-time average speeds. The control layer determines phase composition and adjusts splits at the end of each cycle. The target of this control strategy is to maximize the possibility for vehicles in each direction along the arterial road to pass the local intersection without stop while the utility efficiency of the green signal time is at relatively high level.

**Marwah and Singh (2000):** Simulation studies of traffic flow on urban roads in Kanpur (India) using a two-lane one-way traffic simulation model. Absence of lane discipline in the heterogeneous traffic flow is accounted in the model by treating the entire road space as a single unit instead of a lane. The validation of the model, based on headway distribution and speeds of the different categories of vehicles, indicates that the model can satisfactorily replicate heterogeneous traffic flow on roads where vehicles move without lane discipline.

**The Highway Capacity Manual (HCM 2000):** Utilizes Passenger Car Equivalency (PCE) factors to estimate the effect of heavy vehicles on traffic stream flow behavior under free-flow condition. However, these factors have been (mistakenly) used by professionals to conduct analyses for all traffic conditions i.e. free-flow as well as forced-flow conditions. Recent empirical evidence suggests that the PCE factors for free-flow conditions largely underestimate the effect of heavy vehicles after the onset of congestion.

**Arasan VT. Tamizh and Koshy (2000):** The study proposed a modeling methodology adopted to simulate the flow of heterogeneous traffic with vehicles of wide ranging static and dynamic characteristics. The simulation framework for the traffic-flow model is prepared to consider effect of absence of lane discipline in mixed traffic flow conditions.

**Thamizh Arasan Venkatachalam and Dhivya Gnanavelu (2004):** Have study to check for the validity of the concept, the occupancy and area of area – occupancy of a homogeneous traffic stream were estimate the different length of detection zone through simulation experiment and the value were relate to the density of the steam. Author have been proved the area occupancy, rather than occupancy can be used as indicator of road traffic concentration at any flow level because of it a ability to accurately replicate the extent of usage of the road space.

### III. CONCLUSION

This paper presented literature review on estimation of capacity of four lane divided urban arterial road in Indian Context. Most papers referred in this context are focused on estimating speed and evaluating the effect on speed due to particular sections of the road. It has been observed that the speed may change according to roadway and traffic conditions. In India the urban roads faces wide variety of mixed traffic and disparity in their size, speed and technology.

### IV. REFERENCES

1. B. R. Marwah, Bhuvanesh Singh, “Level of Service Classification for Urban Heterogeneous Traffic a Case Study of Kanapur Metropolis”.
2. C. Jotin Khisty, B. Kent Lall, “Transportation Engineering”, Third Edition Prentice Hall of India Private Limited New Delhi 2008.
3. Dr. Satish Chandra, “Capacity Estimation Procedure for Two Lane Roads Under Mixed Traffic Condition”, Paper no 498.
4. Dr. V. Thamizh Arasan, G. Dhivya, “Measuring Heterogeneous Traffic Flow Density”, World Academy of Science, Engineering and Technology 22, 2008.
5. Dr. V. Thamizh Arasan, Reebu Zachariah Koshy, “Simulation of Heterogeneous Traffic to Derive Capacity and Service Volume Standards for Urban Road”, Paper no 510.
6. Dr. V. Thamizh Arasan, G. Dhivya, “Simulation of Heterogeneous Traffic Flow Characteristics”.
7. Highway Capacity Manual (1985), Special Report 209, Transportation Research Board, National Research Council, Washington, D.C. USA.
8. Kazushi SANO, Chu Cong MINH, Chu Cong MINH, “The Speed, Flow and Headway Analyses of Motorcycle Traffic” , Vol 6, pp.1496-1508, 2005.
9. L. R. Kadiyali, “Traffic Engineering and Transport Planning”, Khanna Publishers, New Delhi, 7<sup>th</sup> Edition, 2007.

10. Ramachandra Rao, “Developing and validation a simulation model for heterogeneous traffic” ,TRB 2009 Annual Meeting CD- ROM.
11. Saad Yousif, “Partial Elliptical Two-Regime Speed-Flow Traffic Model Based on the Highway Capacity Manual”, M5 4WT, United Kingdom.
12. S. L. Dhingra, Ishtiyag Gull, “Traffic Flow Theory Historical Research Perspectives”, July 2008.
13. Siamak Ardekani, Mostafa Ghandehari, Shiva M Nepal, “Macroscopic speed Flow Models for Characterization of Freeway and Managed Lanes”,2011.
14. Thamizh Arsan Venkatachalam,Dhivya Gnanavelu, “Concentration of Heterogeneous Road Traffic”,Volume 47.
15. St Johan’s University U K, Liberia, Journals.