

FACTORS AFFECTING ROAD ACCIDENTS -A REVIEW

Vishwas Malik

Department of Civil Engineering UIET, MDU Rohtak

Email id-vishu.malik73@yahoo.com

Abstract-*One cannot deny that road accidents are a serious concern of the present world. However, most of us do not know the actual causes for the large number of fatalities taking place on roads. We, generally, talk of some or other cause but it is necessary to understand all the probable causes for the accidents. In this paper, we have done an extensive review of literature to understand the causes of the accidents happening on roads. The factors have been categorized in three different types which have multiple sub-factors within.*

Key words: Road safety, Road accidents, Causes, Driver, Environment, Road condition.

I. INTRODUCTION

Road safety is a standout amongst the most imperative issues in our general public. Consistently 1.2 million individuals are murdered and 20 - 50 million people are injured in road mishances. On the off chance that flow patterns proceed with road car crashes are anticipated to be a third driving supporter of the worldwide weight of ailment and damage by 2020[1]. India had earned the questionable qualification of having more number of fatalities due to road mishances on the planet. Road security is rising as a noteworthy social concern around the world especially in India [2]. Accidents are a drain on the national economy and may prompt disablement, death, harm to wellbeing and property, social enduring and general corruption of the earth. To limit the no. of accidents by any sort and seriousness anticipated that would happen on the substance amid a particular period is known as road wellbeing. Mishaps and the fatalities on road are the consequences of the interchange of various elements. There are multiple ways people are commuting like trucks, bikes, rickshaws, pushcarts and tractor trolleys, to different classes of two/three wheelers, engine autos, transports, trucks, and multi-hub business vehicles and so forth. Number of vehicles have increased tremendously but the road infrastructure has not expanded with the same pace and therefore endangering the people in India. In India, the rate of mischance is straightforwardly corresponding to the development of vehicle populace. Road mishaps are a human catastrophe, which includes high human enduring. They force a colossal financial cost as far as inconvenient passing, wounds and loss of potential pay. The consequences of road mishaps can be huge and its negative effect is felt on people, their wellbeing and welfare, as well as on the economy. Thus, road security has become an issue of national concern. Road Safety is a multi-sectoral and multi-dimensional issue. It consolidates the improvement and administration of road foundation, arrangement of more secure vehicles, enactment and law enforcement, mobility planning, provision of health and doctor's facility administrations, youngster wellbeing, urban land use planning etc. In other words, its ambit traverses building parts of both, roads and vehicles on one hand and the arrangement of wellbeing and healing facility administrations for injury cases in post-crash situation.

II. ROAD SAFETY & VARIOUS CAUSES OF ACCIDENT

Road activity wellbeing alludes to techniques and measures for diminishing the danger of a man utilizing the road arrangement being slaughtered or truly harmed. The clients of a road incorporate people on foot, cyclists, drivers, their travelers, and travelers of on-road open transport, fundamentally transports and cable cars. Best practice road wellbeing techniques center around the aversion of genuine damage and passing accidents disregarding human uncertainty. Safe road configuration is presently about giving a road domain which guarantees vehicle velocities will be inside the human resistances for genuine damage and passing wherever struggle focuses exist. The different reasons for mishances might be because of three variables as demonstrated as follows

- (A) Driver
- (B) Vehicle
- (C) Environment

III. REVIEW OF LITERATURE

A) Driver characteristics

I) Age, Gender, and Personality

Iversen, Hilde, and Torbjörn Rundmo [3] endeavored to analyze associations for road mishaps among the components like identity and dangerous driving. They showed that individuals with outrage are more inclined to mischances. Machin, Anthony, and Kim [4] say that the drivers' freshness comes about into not understanding the driving danger circumstance effectively. They likewise underscored the part of components identifying with identity in the road mischances. Tao, Da, Rui Zhang, and Xingda Qu [5] are of the feeling that the identity of an individual does not straightforwardly connect with the mischance chance. Be that as it may, the identity of an individual effects affects driving conduct. Hassan and Aty [6] likewise propose comparable finding in his examination in view of drivers who were youthful.

ii) Alcohol and Drugs

Mayhew, Donelson, Beirness, and Simpson [7] says that intoxicated youthful grown-ups are more inclined to mishaps. Breen et al [8] in their examination considered the criminological post-mortem records of the drivers who lost their life amid road mischances. Shiv Kumar and Krishnaraj [2] think about the utilization of alcoholic material or comparative different things to be one of the unmistakable factors. Vaez and Laflamme, [9] in their investigation which was financed by Swedish National Road Administration uncovers a comparative outcome and observes that smashed heading to be an imperative factor and educated the points of confinement regarding the liquor amid the driving. Anne et al., [10] found an intriguing linkage between the age of the drivers who were smashed and passages in the road mischances and say that if the driver under the liquor is more youthful he or she is more inclined to fatalities. Campus et al., [11] with the assistance of an information in Brazil amid 2007-2009 demonstrated that there is an immediate connection between the fatalities and tanked driving.

iii) Speed

Aarts and Schagen [12] say that speed of the vehicle has coordinate connection with mischances. Lee and Mannering [13] built up an ongoing accident forecast display by taking aggregate travel time and Crash potential diminishment. The examination result showed the variable speed utmost could diminish crash potential by 5-17%. Prabhakhar et al., [14] dissected that giving preparing among drivers decreases speeding conduct. They utilized speed as needy variable and separation as capacity in ANOVA. Golob and Recker [15] investigated mishap in southern California and discovered mischance qualities as an element of activity stream attributes, controlling for lighting and climate condition. The result showed that kind of impact is unequivocally identified with middle movement speed and worldly variety in speed in the left and inside paths. Hit-protest crash including different vehicle that are related with path change moves will probably happen on wet road while backside impacts will probably happen on dry roads amid sunlight controlling climate and light condition.

iv) Fatigue

Houquan et al., [16] investigated hospitalized drivers who were included in road traffic crash between April 2006 to October 2007 in UAE. A calculated model was fitted utilizing the variables like drivers demographic data, time, date, area, instrument of impact, speed at impact and lethargy. The conclusion was rest is a critical factor to road car accident. Further they advised to end driving on highways feeling drowsy particularly amid lunar month of Ramadan. Driver fatigue is a main problem in long journey due to restlessness. Blower et al., [17] watched that 20% of all deadly crash and 10% of all wounds including truck happened between 12AM to 6AM, the pinnacle period for driver weakness.

v) Cell telephones

Tornros and Boiling [18] led an explore different avenues regarding 48 drivers by covering a separation of 15 Km on a country two-path road. They inferred that driving execution lessened by dialing hand held telephone and speed diminished with hands free telephone. Response time to notice sign at road side diminished for hand held telephone client.

vi) Restraints

Sreedharan et al., [19] investigated the determinants utilization of crash caps among motorcyclist in India. A cross-sectional investigation directed in Kerala. The ponders discovered just 73.1% of motorcyclist was not utilizing protective cap which comes about more head wounds amid crash in that locale.

B) Vehicular Characteristics

Vehicle assumes an essential part in a crash. This might be because of imperfect wheel arrangement, tire blasting, brake disappointment, over-burdening, maybe a couple head light deformity, backdrop illumination imperfection, pointer imperfection, controlling imperfection.

i) Tyre Defect

Tire deformity might be expected to under or over expansion, over-burdening, maturing conduct, outer effect because of pothole, garbage, nail and so on. Tires up to six years from the date of maker ought to be changed including save tires (Osueke and Okorie, [20])

ii) Brake Failure

Mishap forces high elusive cost (agony, anguish and suffering). Vehicle mischance can be lethal and constitute a high monetary weight. Oduro [21] studied a no of mishap and found that 83% brake disappointment result in mischance. Brake insufficiency is because of vehicle over-burdening, uneven tire weight, erroneous brake alteration, air in breaking framework, programmed brake agent not working, brake liquid on covering. Brake disappointment is because of broken pipe, low brake liquid level, split brake drum, brakes overheating.

iii) Overloading

One over-burden hub causes harm proportionate to 22 lawfully stacked axles. Over-burden vehicle builds upkeep cost and peril (Osama et al., [22]) Overloading truck diminishes braking capacity of truck, strength of truck, sudden deformity of road and harm of vehicle. Lethal accidents including over-burden vast truck increments by 52% (Chan, [23])

C. Condition Characteristics

i) Road Elements

Roadway configuration is a standout amongst the most critical variables that influence driving conduct and saw security [24]. Basat and Sinar considered joined impact of roadway plan component, for example, bear width, guardrail and roadway geometry (ebb and flow) by taking target driving measures (speed and path position) and subjective measure (perceived safe driving rate and assessed road wellbeing) into account. They found the shoulder width significantly affected genuine speed and path position yet when a monitor rail significantly affected apparent safe driving. Bamzai et al., (25) investigated into security effects of expressway bear characteristics in Illinois. Information were examined to set up relationship between's shoulder related crashes by sort and seriousness classification.

ii) Road Side Features

Somchainuek et al., (26) examined road side security on Thai NH. The outcome demonstrated that speeding vehicles were engaged with roadside crashes represented around 70% of the aggregate accidents and 30% of road side accidents were because of road side trees. Jinsun and Doohee (27) built up a connection between mishap seriousness and roadside highlights. The outcome demonstrates that run-off-roadway mischance can be lessened by maintaining a strategic distance from cut side inclines, diminishing the separation from outside shoulder edge to protect rail, diminishing the no of detached tree along road way segment and expanding the separation from outside shoulder edge to luminaire shafts. Run-go 4x4 romping way mishap is a mind boggling communication of road side factors, for example, nearness of guardrails, incidental settled question, sign backings, tree gatherings and utility posts along the road way.

iii) Signs and Signals

Chen et al., (28) created activity wellbeing model utilizing relapse in New York city. The outcome demonstrates that flag related countermeasure that are intended to diminish strife are part stage, timing, flag establishment, all walker stage and expanding person on foot crossing lessens crashes. Activity quieting measures including road eating regimens are likewise observed to be huge in security benefits. Countermeasures that are intended to caution driver psychological consideration, for example, high perceivability crosswalks and posted speed restrict decrease signs seem to have lesser impact.

iv) Fog and Smoke

Mohmed et al., (29) considered on crash identified with perceivability check because of haze and smoke in Florida. It was discovered that haze smoke related accidents will probably happen around evening time without road lighting prompting more serious wounds. Head-on and Rear-end are regular crashes as far as crash hazard and seriousness. These accidents are more pervasive on rapid road, unified roads, roads without any walkways and two path rustic roads.

v) Volume

Hiselius(30) contemplated the mishap recurrence and homogeneous stream of vehicle. It was discovered that the mischance rate diminishes when the activity stream is homogenous in nature. For Lorries there was a decline in no of mishap and for auto the mischance rate was steady. Golob et al.,(31) made a connection between movement stream and car crash. It was from the examination that implies volume and middle speed influence wellbeing. Path change crashes have a tendency to happen when there is the most astounding inconstancy in speed. While backside crashes tend to bunch where there is a lower variety in speed. There recommendation was to enhance activity building and usage of ITS (Intelligent Transportation System) and improve driver instruction. Kurlaftis and Golias (32) examined between road geometric qualities and mischance rate. They discovered AADT, path width, Serviceability file, contact, asphalt write, get to control are the primary factor adding to mischances. Relative significance was 100% for AADT, 72% for path width, 59% for serviceability, 32% for erosion, 30% for asphalt write and 14% for rustic two-path road. Good LOS has a tendency to happen during the evening when volumes are low. Single vehicle crash rate is higher on the grounds that more drivers are sleepy or less alarm. At the point when activity volume is heaviest multi-vehicle crashes are probably going to happen (Ivan et al., 33).

Caliendo et al.,(34) fitted a Poisson and negative binomial model utilizing mishap as reliant variable and length, ebb and flow, locate remove, side rubbing coefficient, longitudinal slant, nearness of intersection as autonomous variable. Zhuanglin(35) fitted a numerous strategic connection between mishap seriousness and a progression of potential components like-Cross segment, asphalt write, mischance area, activity condition, movement condition, lighting. He found that real mishap was on freeway when contrasted with blood vessel road.

IV. CONCLUSION

In this way we have seen from the researches done in the past that there are multiple reasons for the accidents happening. These reasons has been vastly explained in the researches and certain suggestive measures has also been proposed. Government and the public should look into these researches and should try to obey it.

REFERENCES:

- [1]. Camacho-Torregrosa, Francisco J., Ana M. Pérez-Zuriaga, J. Manuel Campoy-Ungría, and Alfredo García-García. "New geometric design consistency model based on operating speed profiles for road safety evaluation." *Accident Analysis & Prevention* 61 : 33-42. 2013.
- [2]. Sivakumar, T., and R. Krishnaraj. "Road traffic accidents (rtas) due to drunken driving in India-challenges in prevention." *International Journal of research in management and technology* 2, no. 4 : 401-406. 2012.
- [3]Iversen, Hilde, and TorbjörnRundmo. "Personality, risky driving and accident involvement among Norwegian drivers." *Personality and individual Differences* ; 33 (8) : 1251-1263.2002.
- [4] Machin, M. Anthony, and Kim S. Sankey. "Relationships between young drivers' personality characteristics, risk perceptions, and driving behaviour." *Accident analysis & prevention*; 40(2) : 541-547.2008.
- [5] Tao, Da, Rui Zhang, and Xingda Qu. "The role of personality traits and driving experience in self-reported risky driving behaviors and accident risk among Chinese drivers." *Accident Analysis &Prevention* ;99 : 228-235.2017.
- [6].Hassan and Aty. Exploring the safety implications of young drivers attitudes and perceptions, *Accident Analysis and Prevention*;43: pp.45-65.2012.
- [7] Mayhew, D. R., A. C. Donelson, Douglas James Beirness, and Herb M. Simpson. "Youth, alcohol and relative risk of crash involvement." *Accident Analysis & Prevention* 18, no. 4 : 273-287.1986.
- [8] Breen, Jan Mario, PaalAkselNaess, HallvardGjerde, Christine Gaarder, and Arne Stray-Pedersen. "The significance of preexisting medical conditions, alcohol/drug use and suicidal behavior for drivers in fatal motor vehicle crashes: a retrospective autopsy study." *Forensic Science, Medicine and Pathology* 14, no. 1: 4-17.2018.
- [9].Vaez,Lafllame.,Impaired driving and motor vehicle crashes among Swedish youth: An investigation into drivers' sociodemographic characteristics *Accident Analysis and Prevention* ;37: pp.605–611.2005.
- [10]. Anne et al.,, The effects of minimum legal drinking age 21 laws on alcohol-relate driving in the United States *Journal of Safety Research* ;41:pp.173–181,2010.
- [11] Campus et al., The effect of the new traffic law on drinking and driving in Sao Paulo,Brazil *Accident Analysis and Prevention* ;50: pp.622-627.2011.

- [12] Aarts, Letty, and Ingrid Van Schagen. "Driving speed and the risk of road crashes: A review." *Accident Analysis & Prevention* 38, no. 2 (2006): 215-224.
- [13] Lee, Jinsun, and Fred Mannering. "Impact of roadside features on the frequency and severity of run-off-roadway accidents: an empirical analysis." *Accident Analysis & Prevention* 34, no. 2 (2002): 149-161.
- [14] Prabhakaran, Prasannah, Brett RC Molesworth, and Julie Hatfield. "Impairment of a speed management strategy in young drivers under high cognitive workload." *Accident Analysis & Prevention* 47 : 24-29.2012.
- [15] Golob and Recker, *Journal of Transport Engineering* (4), pp-129-66, 2003
- [16] Houquani et al.,(2012) Sleep related collisions in United Arab Emirates, *Accident Analysis and Prevention*.50, pp.1052-1055.2012.
- [17] Blower et al., *Fatalities and Injuries in Truck crashes by Time of day*, University of Michigan Transport Research Institute, 1998.
- [18] Törnros, Jan EB, and Anne K. Bolling. "Mobile phone use—effects of handheld and handsfree phones on driving performance." *Accident Analysis & Prevention* 37, no. 5 (2005): 902-909.
- [19] Sreedharan, Determinants of safety helmet use among motorcyclists in Kerala, India *Journal of Injury and Violence Research*, 2(1) (2010).
- [20] Osueke, C. O., and D. C. Uguru-Okorie. "The role of tire in car crash, its causes, and prevention." *International Journal of Emerging Technology and Advanced Engineering* 12 : 54-57. 2012.
- [21] Oduro, Seth Daniel. "Brake failure and its effect on road traffic accident in Kumasi Metropolis, Ghana." *International Journal of Science and Technology* 1, no. 9 (2012): 448-454.
- [22] Yassenn, Osama Mahmoud, Mohamed Ahmed Hafez, IntanRohaniEndu, IrBahardin Bin Baharom, and MdYunusAbWahab. "Axle load distribution and overloading at the central part of the North-south expressway in Malaysia." *European Journal of Scientific Research* 79, no. 2 (2012): 298-309.
- [23] Chan, Ying Chuen Maple. "Truck overloading study in developing countries and strategies to minimize its impact." PhD diss., Queensland University of Technology, 2008.
- [24] Ben-Bassat, Tamar, and David Shinar. "Effect of shoulder width, guardrail and roadway geometry on driver perception and behavior." *Accident Analysis & Prevention*, 43(6) : 2142-2152.2011.
- [25] Bamzai, Radhika, Yongdoo Lee, and Zongzhi Li. *Safety impacts of highway shoulder attributes in Illinois*. 2011.
- [26] Somchainuek, Opas, PichaiTaneerananon, and SaravutJaritngam. "Investigation Roadside Safety on Thai National Highways." *Indian Journal of Science and Technology* 6, no. 1 2013.
- [27] LEE, Jinsun, and Doohee NAM. "RUN-OFF-ROADWAY ACCIDENT FREQUENCY MODELS BY TYPE OF ACCIDENT SEVERITY." *Journal of the Eastern Asia Society for Transportation Studies* 5 (2003).
- [28] Chen, Li, Cynthia Chen, Reid Ewing, Claire E. McKnight, Raghavan Srinivasan, and Matthew Roe. "Safety countermeasures and crash reduction in New York City—Experience and lessons learned." *Accident Analysis & Prevention* 50 : 312-322.2013.
- [29] Abdel-Aty, Mohamed, Al-AhadEkram, Helai Huang, and Keechoo Choi. "A study on crashes related to visibility obstruction due to fog and smoke." *Accident Analysis & Prevention* 43, no. 5 (2011): 1730-1737.
- [30] Hiselius, Lena Winslott. "Estimating the relationship between accident frequency and homogeneous and inhomogeneous traffic flows." *Accident analysis & prevention* 36, no. 6 : 985-992.2004.
- [31] Golob, Thomas F., Wilfred W. Recker, and Veronica M. Alvarez. "Freeway safety as a function of traffic flow." *Accident Analysis & Prevention* 36, no. 6 (2004): 933-946.
- [32] Karlaftis, Matthew G., and IoannisGolias. "Effects of road geometry and traffic volumes on rural roadway accident rates." *Accident Analysis & Prevention* 34, no. 3 (2002): 357-365.
- [33] Ivan, John N., Chunyan Wang, and Nelson R. Bernardo. "Explaining two-lane highway crash rates using land use and hourly exposure." *Accident Analysis & Prevention* 32, no. 6 (2000): 787-795.
- [34] Caliendo, Ciro, Maurizio Guida, and Alessandra Parisi. "A crash-prediction model for multilane roads." *Accident Analysis & Prevention* 39, no. 4 (2007): 657-670.
- [35] Ma, Zhuanglin, Chunfu Shao, HaoYue, and Sheqiang Ma. "Analysis of the logistic model for accident severity on urban road environment." In *Intelligent Vehicles Symposium, 2009 IEEE*, pp. 983-987. IEEE, 2009.