

To Understand the Various Filtering Techniques with FIR Filters

Mr. Rajesh Uday¹, Mr. Gaurav Phulwari², Ms. Nidhi Verma

¹M.Tech Scholar, Electronics & Comm., Bhagwant University, Ajmer, India, er.gauravphulwari@gmail.com

²M.Tech Scholar, Electronics & Comm., Bhagwant University, Ajmer, India, er.gauravphulwari@gmail.com

³Assistant Professor, Electronics & Comm., Bhagwant University, Ajmer, India, verma.nidhi17@gmail.com

Abstract—In digital system, interference is mixed within the signal that features a nice influence on the performance of the system. Therefore, process of signal needs to be done to induce helpful signal. Finite impulse response (FIR) filter plays a crucial role within the process of digital signal. Planning the FIR filter by MATLAB will alter the sophisticated computation in simulation and improve the performance. By victimization the ways of window perform, frequency sampling and biconvex optimisation techniques, the look of FIR filter has been processed by MATLAB. Within the read of the designed program of MATLAB and that we will get the amplitude-frequency characterization. FIR digital filters are designed to method the signal supported the MATLAB perform, the filtering result of various digital filters is analyzed by examination the signal's amplitude-frequency diagrams that are generated. The experimental results show that the FIR filters designed are effective.

Keywords—FIR filter, MATLAB, window function, frequency sampling, optimisation, amplitude-frequency characterization.

I. INTRODUCTION

The digital filter may be a separate system, and it will do a series of mathematic process to the sign, and so get the required data from the sign. The T.F for a linear, time-invariant, digital filter is typically expressed as:

$$H(z) = \frac{\sum_{j=0}^M b_j z^{-j}}{1 + \sum_{i=1}^N a_i z^{-i}}$$

Where a_i and b_j are coefficients of the filter in Z-transform.

There are several types of digital filters, and additionally many alternative ways that to classify them. According their operate, the FIR filters is classified into four classes, that are low pass filter, high pass filter, band pass filter, and band stop filter. In keeping with the impulse response, there are sometimes two forms of digital filters, that are finite impulse response (FIR) filters and infinite impulse response (IIR) filters. In keeping with the formula higher than, if a_i is often zero, then it's a FIR filter, otherwise, if there's a minimum of one none-zero a_i , then it's Associate in Nursing IIR filter. The three basic arithmetic units required to style a digital filter are: the adder, the delay, and therefore the multiplier factor [1][2]. The following are the steps for coming up with a digital filter:

- Ensure of the property of a digital filter in keeping with the given necessities.
- Use a distinct linear time-invariant system operates to approach to the properties.
- Create use of algorithms to style the system operate.
- Use a technique or hardware to realize it.

II. FIR FILTER

The finite impulse response (FIR) filter is one of the most important basic components in a DSP system. It will guarantee a strict linear part frequency characteristic and amplitude frequency characteristic. Besides, the unit impulse response is finite, thus FIR filters square measure stable system. The FIR filter has abroad application in several fields, reminiscent of telecommunication, image process, and so on [5].

The system operates of FIR filter is:

$$H(z) = \sum_{n=0}^{L-1} h[n] z^{-n}$$

Where $h[z]$ is the impulse response and, L is the length of the filter.

III. IIR FILTER

The infinite impulse response (IIR) filter is algorithmic structure, and it's a circuit. The exactitude of amplitude frequency characteristic is incredibly high, and IIR filters aren't linear section [4]. The input and therefore the output signals are connected by:

$$y(n) = \sum_{k=0}^{\infty} h(k)x(n-k)$$

Where $h(k)$ is that the impulse response sequence wherever $k = \text{zero}, 1, \dots$,

From this equation we tend to see that, for IIR filters, the impulse response is of infinite length.

The IIR filtering equation is expressed as:

$$y(n) = \sum_{k=0}^{\infty} h(k)x(n-k) = \sum_{k=0}^M b_k x(n-k) - \sum_{k=0}^N a_k y(n-k)$$

Where a_k and b_k are the filter coefficients. From equation we tend to note that, the present output sample, $y(n)$ could be operate as past values of output and also the present and past input samples, that's the feedback system. The equation reduces to the FIR equation once the b_k are set to zero and that we note that within the FIR filter current output sample, $y(n)$ could be a operate solely of past and present values of input sample [12][13].

IV. COMPARISON OF FIR AND IIR FILTERS

Table 1. Comparison between IIR and FIR filter

S.No	IIR	FIR
1.	IIR filters are unstable	FIR filter are unstable
2.	Difficult to control phase	Linear phase Response
3.	Only for lower order	Can be used for higher order
4.	Lesser Computation	Large computation
5.	They are Recursive Filters	They are Non Recursive filters
6.	Storages units are lesser	Storage units are more
7.	FFT cannot be used	FFT technique can be used

V. SIMULATION OF ELECTRONIC COMMUNICATIONSYSTEM

The conception of Telecommunications and Electronic systems simulation

System simulation technology refers to theoretical account technology that developed since 1970 combining fashionable computers and simulation code. Theoretical account has high preciseness, skilfulness, smart repeatability, fast modelling and low price benefits. Particularly in recent years, MATLAB, a scientific computing and system simulation language, is developed chop-chop [6]. It's much more convenient to use and operate other than traditional C or C++ language. Alleged transmission system simulation is that the use of the pc on the physical model or mathematical model of actual transmission systems testing and study of this model take a look at on an actual system performance and in operation state. Once a pilot study in actual transmission system is tougher or not possible to attain, the simulation technology has become associate degree inevitable alternative [5].

Steps of computer simulation

- Analyze the simulation system
- Build a system mathematical model
- Collect knowledge
- Establish simulation model on pc
- Verify the simulation model
- Confirm the simulation model
- Design simulation experiment
- Run the pc simulation model
- Analyse results of the simulation

VI. DESIGN OF FIR FILTER

It is necessary to specify pass band, stop band, and transition band once planning a frequency-selective filter. In pass band, frequencies are required to be passed un - attenuated. In stop band, frequencies have to be compelled to be passed attenuated. Transition band contains frequencies that square measure lying between the pass band and stop band. Therefore, the whole frequency vary is split into one or maybe additional pass bands, stop bands, and transition bands [10]. In sensible, the magnitude isn't necessary to be constant within the pass band of a filter. A tiny low quantity of ripple is sometimes allowed within the pass band. Similarly, the filter response doesn't to be zero within the stop band. A small, nonzero price is additionally tolerable within the stop band [14].




Fig.1. Amplitude-Frequency characteristic of low pass filter

The transition band of the filter is between the pass band and also the stop band. The frequency ω_p denotes the edge of the pass band, and the band-edge frequency ω_s defines the edge of the stop band. So, the difference of ω_s and ω_p is the width of the transition band, i.e. $\omega_t = \omega_s - \omega_p$. The ripple in the pass band of the filter is denoted as δ_p , and the magnitude of the filter varies from $1 - \delta_p$ to $1 + \delta_p$. δ_s is the ripple in the stop band. Sometimes we tend to use a graduated table to indicate the frequency response, hence, the ripple in the pass band is $20\log 10\delta_p$ dB, and the ripple in the stop band is $20\log 10\delta_s$ dB. The characteristics of digital filters square measure usually lay out in the frequency domain [8]. The amplitude – frequency response of FIR and IIR filter is commonly laid out in the shape of a tolerance and is given within the figure one. Pertaining to the figure higher than, the subsequent parameters square measure of interest:

- Peak pass band deviation (or ripples)
- Stop band deviation
- Pass band edge frequency
- Stop band edge frequency

VII. VARIOUS TECHNIQUES OF FILTERS

The various filter techniques used to remove unwanted signal i.e.

- Optimum Equiripple Method
- Frequency Sampling Method
- Window Method

Optimum Equiripple Method

Historically, the window operate technique was the primary technique for planning linear-phase FIR filters. The frequency sampling technique and optimized equiripple technique were developed within the Nineteen Seventies and became extremely popular since then. Lacking precise management of the required frequencies, like ω_p and ω_s , is that the most serious disadvantage of the window operate technique within the style of an occasional pass FIR filter. The frequency sampling method is better than the window method in the aspect that the real-valued frequency response characteristics $H_r(\omega)$ is specified, which may be either zero or unity in the least frequencies, except the transition band [8]. The Chebyshev approximation technique offers fully management of the filter necessities. As a result, this technique is additional desirable than the opposite two. It's supported the Remez exchange algorithmic rule that minimizes the error with relevancy the max-norm.

From the figures below i.e. 10,11,12,13, it's straightforward to check that the input is created of two superposition signals with distinct frequencies. The pass band is from zero to 500Hz, and also the stop band is from five hundred to 1000Hz. once filtering, the signal with frequency of 400Hz is unbroken, whereas the signal with frequency of 700Hz that is within the stop band is filtered [15].




Fig.2. Time-domain before filtering




Fig.3. Time-domain after filtering




Fig.4. Frequency-domain before filtering




Fig.5. Frequency-domain after filtering

Frequency Sampling

The frequency sampling technique can add following approach, we have a tendency to begin within the frequency domain, and sample the desired frequency response $H(e^{j\Omega})$ with N evenly-spaced samples instead of a continuous frequency, and get $H_d(k) = H_d(e^{j\Omega})|_{\Omega=2\pi k/N}$, ($k=0,1,\dots, N-1$). Then, let $H(k) = H_d(k) = H_d(e^{j\Omega})|_{\Omega=2\pi k/N}$, we have a tendency to get the unit impulse response, $h(n) = \text{IDFT}[H(k)]$, wherever IDFT is Inverse discrete Fourier transform. The inverse DFT then yields an impulse response which is able to cause a filter whose frequency response is equivalent to that of the specification specifically at the placement of the frequency samples. The advantage of this technique is that we are able to style filters directly within the frequency domain, but the disadvantage is that the sampling frequency can only be integer times of $2\pi/N$, and that we cannot guarantee a random cut-off frequency.

From the figures 6,7,8,9 we are able to get the knowledge that the signal is created from three superposition signals with distinct frequencies. The oftenness is 2000Hz, and also the pass band is from zero to 500Hz, therefore signals with the frequencies of 100Hz and 300Hz area unit unbroken, whereas that of 700Hz is filtered.




Fig.6. Time-domain before filtering




Fig.7. Time-domain after filtering




Fig.8. Frequency-domain before filtering




Fig.9. Frequency-domain after filtering

Window Method

In this technique, a truncated ideal low pass filter with a particular information measure is generated, and so a window is chosen to urge sure stop band attenuation. The length of filter “L” can be adjusted to meet a specified roll-off rate in the transition band. The windowed, truncated low pass filters is taken into account and so different reasonably filters, like high pass, band pass, and band stop filters may be achieved by many techniques [17]. Any finite-length of the best low pass impulse response could also be thought-about because the product of the infinite-length low pass impulse response could also be thought-about because the product of the infinite-length low pass impulse response and a window operate W, that incorporates a finite variety of contiguous nonzero-valued amplitudes [6].

Comparing Figures two,3,4,5 it's simple to visualize that the signal is created from two superposition signals with totally different frequencies. The pass band is 0-100 cycles/second, and stop band starts from 170Hz, and there are two frequencies of 100Hz and 200Hz eager to be filtered. The signal with frequency of 100Hz that is within the vary of pass band is unbroken, whereas the signal with frequency of 200Hz that is within the vary of stop band is filtered. The minimum stop band attenuation values for playing window is 53dB, that is bigger than 50dB, and this result specifically meets the necessities [8].




Fig.10. Time-domain before filtering




Fig.11. Time-domain after filtering




Fig.12. Frequency-domain before filtering




Fig.13. Frequency-domain after filtering

VIII. CONCLUSION

Out of all FIR Filtering techniques, OPTIMUM EQUIRIPPLE technique is that the best technique for filtering, as a result of:

- 1.Minimizes most ripple
- 2.Precise management of the crucial filter frequencies
- 3.Can be easily designed on computer that's why called computer aided design
- 4.Ideal linear part style
- 5.Approximate error between desired frequency response & actual frequency response is unfold equally across pass band and stop band
- 6.Sharpest FIR filter

REFERENCES

- [1] <http://www.mathworks.com/access/helpdesk>.
- [2] T.W. Parks and C.S. Burrus, Digital Filter Design.
- [3] L.R. Rabiner and B. Gold, Theory and Applications of Digital Signal Processing.
- [4] J.G. Proakis and D.G. Manolakis, Digital Signal Processing-Principles, Algorithms.
- [5] L.R. Rabiner, B. Gold and C.A. McGonegal, "An approach to the Approximation".
- [6] Zhenhe Sun, Wei Yu, Chen He, "FIR digital filter design and MATLAB simulation", 2012 International Conference on Measurement, Information and Control (MIC) pp 677 – 680.
- [7] Alia Ahmed Eleti and Amer R. Zerek, "FIR Digital Filter Design By Using Windows Method With MATLAB", IEEE, 14th International Conference on Sciences and Techniques of Automatic control & Computer Engineering, Sousse, Tunisia, pp. 282-287, 2013.
- [8] Sonika Gupta, Aman Panghal "Performance analysis of FIR Filter Design by using Rectangular, Hanning and Hamming Windows methods" International Journal of Advanced Research in Computer Science and Software Engineering, Vol.2, Issue 6, pp. 273-277, 2012.
- [9] Shalu Pandey, Surabhi Agrawal, Urvashi Agrahari, "FIR filter implementation and its performance analysis", International Journal of Advanced Technology & Engineering Research, ISSN: 2250-3536, Vol. 3, Issue 3, pp. 2013.
- [10] Forester W. Isen. *DSP for MATLAB™ and Lab VIEW™*.
- [11] John G. Proakis. Dimitris G. Manolakis. *Digital Signal Processing*. Fourth Edition. 2007.
- [12] James H. McClellan. Ronald W. Schafer. Mark A. Yoder. *Signal Processing First*. 2003.
- [13] Stephen Boyd. Lieven Vandenberghe *Convex Optimization*, 2004.
- [14] L.R. Rabiner and B. Gold, *Theory and Applications of Digital Signal Processing*.
- [15] J.G. Proakis and D.G. Manolakis, *Digital Signal Processing Principles, Algorithms*.
- [16] Problem for Nonrecursive Digital Filters," *IEEE Trans. Audio and Electroacoustics*.
- [17] <http://www.mathworks.com/access/helpdesk/help/toolbox/signal/signal.shtml>.
- [18] Signal Processing Toolbox, The Mathworks, Inc.
- [19] Problem for Nonrecursive Digital Filters," *IEEE Trans. Audio and Electroacoustics*,