

EXAMINATION OF TRAFFIC VOLUME AND SPOT SPEED ON A BUSY CORRIDOR (NH-146, VIDISHA)

Sarvesh Yadav¹, Dr. Y.P.Joshi²

¹Transport Engineering, M.Tech Scholar, SATI VIDISHA, MP, INDIA

²Transport Engineering, Professor, SATI VIDISHA, MP, INDIA

Abstract—*Speed is a critical transportation thought since it identifies with wellbeing, time, solace, comfort, and financial aspects. Spot speed considers are utilized to decide the speed dispersion of an activity stream at a particular area. Activity clog, not constrained to but rather particularly pervasive in metropolitan urban areas, is a standout amongst the most obviously declining issues related with movement designing and urban arranging, with clear ramifications on circles of urban economy, condition and way of life. Activity in urban communities keeps on developing transiently particularly in real urban areas of creating nations, which are portrayed by overwhelming monetary and populace development. This normally requires exceptional transportation of merchandise and travellers, expanding interest for individual vehicular possession that in the course of the most recent decade has seen exponential development around the world. In any case, the disappointment of adequately fast infrastructural advancement required to take into account this expanding activity as often as possible prompts disappointments of the urban transportation framework, bringing about congested driving conditions. From designing perspective, killing blockage isn't practical, however diminishing it fundamentally by making compelling utilization of activity development examples and system administration absolutely is. Urban streets are portrayed by blended movement conditions, bringing about complex collaboration between different sorts of vehicles. To take into account this, it is normal to express the limit of urban streets regarding a typical unit. The unit by and large utilized is the 'Traveler Car Unit, (PCU), and every vehicle compose is changed over into equal PCUs dependent on their relative impedance esteem. For concentrate chosen field region is from Shubham Automobile to Hero Motocorp by means of NH-146, Vidisha for which Stop watch technique utilized for the roadway to distinguish the passing vehicles.*

Keywords—*Spot Speed, Traffic Volume, PCU, Stop Watch, Vidisha, NH-146.*

I. INTRODUCTION

Travel time is a major proportion of framework adequacy in transportation and is exceptionally valuable for the voyagers and framework administrators. Giving travel time data before beginning of voyage to the street clients enables them to settle on a more educated course decision choices which thusly enable the framework by appropriating the movement to request. With an expansion in populace comes more activity, and with more movement comes the need to update, restore, or supplant existing transportation foundation. Amid the vital development there is a need to control the measure of postpones that drivers will understand. An essential piece of controlling postponement is to take a gander at the reason for deferral. Indian movement condition contrasts from the activity state of nations like USA as far as (i) absence of path control and (ii) nearness of greatly heterogeneous movement including mechanized and non-mechanized vehicles.

Activity blockage is a transient condition on systems that happens as utility increments, and is described by slower speeds, longer outing occasions, and expanded lining. At the point when volume of movement is high thus heterogeneous that the communication between vehicles backs off the speed of activity, movement clog is the outcome. Speed is an essential transportation thought since it identifies with wellbeing, time, solace, comfort, and financial matters. Spot speed ponders are utilized to decide the speed dispersion of an activity stream at a particular area. The information accumulated in spot speed thinks about are utilized to decide vehicle speed percentiles, which are valuable in settling on many speed-related choices. Spot speed information have various security applications, including the accompanying (Robertson 1994):

1. Deciding existing movement tasks and assessment of activity control gadget.
2. Setting up roadway outline components.
3. Evaluating roadway security questions.
4. Observing movement speed inclines by orderly on-going pace ponders.
5. Estimating adequacy of movement control gadgets or activity programs, including signs and markings, movement operational changes, and speed authorization programs.

Essentially, there are two sorts of speed: the time-mean speed and the space-mean speed.

Space Mean Speed: It is the length of a street segment separated by the normal travel time of a few vehicles over this particular area.

Time Mean Speed or Spot Speed: It is the normal spot speed of a few vehicles estimated at a given spot.

For geometric plan of streets, it is important to have a reasonable gauge of the rates at which vehicles travel. In view of the speed thinks about, the outline speed can be chosen, and other geometric components of plan, for example, flat shape, vertical profile, locate separations and super-rise can be resolved.

Spot Speed examines are directed to evaluate the circulation of rates of vehicles in a surge of movement at a specific area on an expressway.

1.2 Methods of spot speed estimations

Techniques for leading spot speed Studies are partitioned into two primary classes: Manual and Automatic. Spot rates might be assessed by physically estimating the time it takes a vehicle to go between two characterized focuses on the roadway a known separation separated (short separation), typically under 90m. Separation between two is by and large relying on the normal speed of movement stream. Following tables gives suggested consider length (in meters) for different normal stream speed ranges (in KMPH)

- Stop Watch Method
- Radar Method
- Pneumatic Tube Method
- Inductive Detector Loop (IDL)
- Electronic-Principle Detectors (Photography)
- Piezoelectric sensors

II. LITERATURE REVIEW

Movement clog is a worldly condition on systems that happens as utility increments, and is described by slower speeds, longer trek times, and expanded lining. At the point when volume of movement is high thus heterogeneous that the collaboration between vehicles backs off the speed of activity, movement blockage is the outcome. As interest approaches the limit of a street (or of the crossing points along the street), movement clog sets in. At the point when vehicles are completely halted for the timeframe, this is conversationally known as congested driving conditions.

To plan a roadway there are particular street components that must be resolved. A portion of these are the quantity of paths, path width, middle compose and width, length of quickening and deceleration paths for on and exit ramps, requirement for truck climbing paths for roadways with soak levels, bend radii required for vehicle turning, and the roadway arrangement required to give satisfactory ceasing and passing sight separate (Mannering and Kilareski 1998). The Geometric highlights of the street, for example, flat and vertical arrangement locate remove and by and large, cross-segment, are delicate to the plan speed.

2.1 Traffic Survey

Activity designers and organizers require data about movement. They require data to outline and oversee street and movement framework. They utilize the data for arranging and outlining movement offices, choosing geometric gauges, financial investigation and assurance of needs. They utilize this to legitimize warrant of movement control gadgets, for example, signs, activity signals, asphalt markings, school and person on foot intersections. The likewise utilize this data to think about the viability of presented plans, diagnosing given circumstances and finding proper arrangements, anticipating the impacts of anticipated procedures, adjusting and approving activity models. Transportation framework is a dynamic framework. Data about activity must be frequently refreshed to keep pace with consistently changing transportation framework. Information must be gathered and dissected methodically to get delegate data. Activity reviews are the methods for acquiring data about movement. This is a precise method for gathering information to be utilized for different movement building purposes.

2.2 Main motivations behind activity study

The fundamental motivations behind movement review are: activity observing, movement control and administration, movement authorization, activity estimating, show adjustment and approving and so on.

2.3 Parts of traffic studies

Movement examines include:

- *Inventory of street activity physical highlights*

- *Traffic stream qualities volume, speed, thickness, inheritance thinks about and so forth.*
- *Capacity investigations of avenues and convergences*
- *System utilization examines Travel time and deferral, O-D study*
- *Travel request home meeting study*
- *Road client's cost-Value of movement time, vehicle working expense*
- *Parking supply and request contemplates*

Spot speed studies ought to be directed on occasion when the street fragment encounters "free-stream" driving conditions [1]. Besides, neighbourhood law authorization and different authorities, for example, Dubai Police Department, should be reached and endorsements ought to be allowed before leading a spot speed think about.

As per an examination directed in 2002, there are around 1 million yearly fatalities worldwide because of car crashes, and around 10 million for all time crippled each year. Constantly 2020 estimations demonstrate that auto collisions will turn into the third driving plague in fatalities around the globe, gone before by clinical melancholy and coronary illness. In the UAE, car crash fatalities fundamentally surpass those of other industrialized nations of Europe and the United States. In addition, the investigation reasoned that car crashes are the second most driving reason for fatalities in the UAE. Among best positioned potential reasons for car crashes is surpassing as far as possible and driving thoughtlessly [2].

In view of the car crashes that happened somewhere in the range of 1995 and 1999, Dubai has the most noteworthy casualty rates per 100,000 populace and enlisted vehicles contrasted with alternate nations in the gathering.

In another examination in London, UK, Walter et al. [3] displayed the effect of expanding the police requirement inside a urban territory. The specialists detailed the impact of setting speed radars and more static and versatile police authorization that are effortlessly unmistakable by the drivers. The creators inferred that there was an orderly speed decrease along the considered hall because of the utilization of the implementation measures. Be that as it may, there was no impact of these authorization measures on the utilization of safety belts and cell phones.

Dowling and Holloman [4] directed an investigation to decide the best method to position or show implementation speed controls, for example, radars. They showed that the reason for movement implementation isn't just to issue tickets for drivers damaging the posted speed, yet in addition to adjust the drivers about the apparent hazard related with speeding conduct.

Liu et al. [5] broke down the impact of controlling the speed out and about system utilizing radars and cameras. The outcomes demonstrated that three radars limitedly affect the speed. Then again, the cameras indicated much better impact on constraining the paces.

The adequacy of speed authorization on interstates has been assessed by Xu et al. [6]. They presumed that the adequacy of robotized speed authorization relies upon the area of the requirement gadget. The impact on rates may stretch out to around 2 km, when the speed implementation gadget is settled on cantilevers. Be that as it may, street side speed requirement demonstrated an impact of around 1 km as it were.

Dowling and Holloman [7] led an investigation to decide the best method to position or show authorization speed controls, for example, radars. They demonstrated that the reason for movement implementation isn't just to issue tickets for drivers damaging the posted speed, yet in addition to modify the drivers about the apparent hazard related with speeding conduct.

Another examination was directed on the rustic streets in the Dutch territory Friesland. Authorization was predominantly executed by methods for versatile radars. The assessment secured a time of 5 years of implementation, where the speed information demonstrated an incredible decline in mean speed and the level of speed restrain violators after some time. The biggest of these abatements was seen in the principal year of the authorization usage, and furthermore in the fourth year, when implementation was fortified. Reductions in mean speed and number of violators were likewise seen on an adjacent roadway that was not subjected to implementation radars because of the overflow impact.

III. METHODOLOGY

The aim of this section is to clarify the system which will embrace in this present investigation. For concentrate chosen field region is from Shubham Automobile to Hero Motocorp on NH 146, Vidisha for which stop watch technique is utilized to distinguish the passing vehicles. Speed is an essential proportion of the nature of movement and security of street organize. Speed by definition is the rate of development of vehicle in separation per unit time. A run of the mill unit of speed is kilometres every hour (KMPH) or miles every hour (mph). The primary reason for this examination is to decide activity parameter, exceptionally speed. Spot Speed estimations are frequently taken at a point (or a short segment) of street path under states of free stream.

To think about the speed attributes a stretch, it ought to fulfil some stretch determination criteria. Those are made reference to beneath:

3.1 Stretch Selection Criteria

Coming up next are the fundamental highlights that a chose stretch should fulfil to get exact outcomes:

- Any area might be utilized for arrangement of a particular activity designing issue.
- The geometry of street ought to be plain, with no hero worship or incline.
- For precise outcomes, choice an area where is street condition is great and where drivers drive serenely.
- Intersections joining or redirecting movement ought not to interfere with the activity stream or speed of the vehicles passing the stretch.
- The stretch ought to be free from speed breakers, precautionary measure signs and so forth..., and the drivers ought to have the capacity to go with their characteristic style.
- Experimentation ought to be done in the season of free movement stream.
- Mainly the drivers ought not to know about the test going on, he might be diverted.

3.2 Experimentation

The hardware required to do stop watch strategy are

- Stop observe
- Measuring Tape
- Flag

We require somewhere around three onlookers to do the investigation. In the wake of picking a segment that fulfils the above criteria, 30 meters extend is estimated utilizing an estimating tape. Two spectators, one Spectator remains at the completion purpose of the stretch.




Fig 1. Map of study.




Fig 2. Aerial view of study.

IV. DATA COLLECTION AND ANALYSIS

The outcomes and investigation of the examination are critical to guarantee that the key targets can be accomplished. Anticipated that outcome vital would draw up at beginning period before the task done, to be contrasted and the real outcome. After the investigation is finished and the information have been classified the accompanying advances might be considered as a component of the ordinary information examination. In particular, the thought is recognize key parameters related with roadway speeds, which may incorporate any or the majority of the accompanying:

1. *Mean Speed*: The normal speed; figured as the entirety of all paces isolated by the quantity of speed perceptions.
2. *85th Percentile Speed*: The speed at or underneath which 85 percent of an example of free streaming Vehicles is voyaging; this is regularly utilized as a benchmark for building up the speed dependent on a spot speed examine.
3. *95th Percentile Speed*: The speed at or beneath which 95 percent of an example of free streaming vehicles is voyaging (in view of a spot speed ponder).
4. *Middle (50th Percentile Speed)*: The speed that similarly isolates the circulation of spot speeds; 50 percent of watched speeds are higher than the middle; 50 percent of watched speeds are lower than the middle.
5. *Mode*: The number that happens most every now and again in a progression of numbers.
6. *Speed Variance*: The distinction in movement speeds for vehicles out and about. Scientifically, change is the normal of the squares of the distinction to the mean for each watched speed.
7. *Pace*: A 10 mile-per-hour augment in rates that envelops the most astounding bit of watched speeds; frequently is the mean speed in addition to/less five miles for every hour.

In dissecting spot speed information various noteworthy qualities are acquired. A portion of these qualities are registered straightforwardly from the information while others are resolved from a realistic portrayal. In dissecting spot speed information various critical qualities are acquired. A portion of these qualities are registered specifically from the information while others are resolved from a realistic portrayal

4.1 Traffic Volume Count Survey:

Movement volume review was done at the areas in the chose stretches to know the aggregate volume of activity, organization of activity and hourly variety of movement. Activity volume tallies at a hour interim were taken at every one of these areas to process crest hour movement stream attributes.



Fig 3. Marking of starting point for spot speed data Collection.

Table 1
Traffic Volume: Shubham Automobile to Hero Motocorp on 28-05-2018
From 7:30am on 28-05-2018

Location: Shubham Automobile, Head north-west on NH-146					Direction: From: Shubham Automobile to Hero Motocorp
Time	BUSES	TRUCKS	CARS	AUTORICKSHAWS	2-WHEELERS
7:30 to 8:30	28	30	65	42	125
8:30 to 9:30	25	27	85	46	158
9:30 to 10:30	32	25	102	51	120
10:30 to 11:30	18	29	99	58	119
16:30 to 17:30	10	22	115	34	170
17:30 to 18:30	28	28	101	36	176
18:30 to 19:30	35	26	88	55	160
19:30 to 20:30	16	20	86	60	162
20:30 to 21:30	19	22	113	34	150
21:30 to 22:30	30	28	98	28	108

Similarly the above data's are taken from 29-05-2018 to 31 -05-2018

Numerous substantial trucks recorded are likewise made in medium obligation adaptations:

- Concrete transport truck (concrete blender)
- Mobile crane.

- Dump truck.
- Garbage truck.
- Log bearer.
- Refrigerator truck.
- Tractor unit.
- Tank truck.




Fig 4. Hourly Variation of Buses Traffic Volume on different days.




Fig 5 Hourly Variation of Trucks Traffic Volume on different days.




Fig 6 Hourly Variation of Cars Traffic Volume on different days.




Fig 7 Hourly Variation of Auto-Rickshaws Traffic Volume on different days.



Fig 8 Hourly Variation of Two wheelers Traffic Volume on different days.

4.2 Spot Speed Analysis:

Spot speed information was gathered on a testing premise at ordinary with the activity volume tallies amid day time and night time. Spot speeds at various areas according to heading and diverse vehicle composes were recorded and sustained into PCs in Excel arrange for investigations. Hourly variety of spot speeds was broke down to get most extreme and least watched speeds according to heading for stream and also mean velocities, 85th percentile rates and they are displayed.

4.2.1 Spot Speed Analysis for 28-05-2018

The arithmetic average or mean speed is the most frequently used speed statistic. It is a measure of the central tendency of the data and is computed from the formula:

$$\bar{v} = \frac{\sum f_i v_i}{\sum f_i}$$

$$\bar{v} = \frac{13360}{290}$$

$$\bar{v} = 46.069 \text{ km/hr}$$

Where: $\bar{v}$ = mean or average speed.

$\sum f_i v_i$ = sum of the mean frequencies.

$\sum f_i$ = total number of vehicles observed.

Information gathered at a point over some undefined time frame, e.g.: by stopwatch or radar meter, deliver speed disseminations in time, whose methods are time mean velocities. Information got over a stretch of street immediately as by two progressive photos, result in speed appropriation in space and space mean velocities. These dispersions are not the equivalent; time mean speed is higher than space mean speed. This can be comprehended on the off chance that one envisions a segment of expressway; a spot speed test toward one side assumed control over a limited timeframe will have a tendency to incorporate some quick vehicles which had not yet entered the segment toward the beginning of the overview, yet will bar a portion of the slower vehicles which were inside the roadway segment when the example was begun.

Table 2
 Percentage analysis of spot speed data 28-05-2018

Speed class(Km/hr)	Class Mid value v_i	Class frequency (number of observations in class) F_i	$F_i * v_i$	Percentage of observation in class	Cumulative percentage of all observation	$F_i * (v_i - \bar{v})^2$	
21-25	23	22	460	6.90	6.90	10738.83	
26-30	28	25	728	8.97	15.87	8585.761	
31-35	33	27	891	9.31	25.18	4684.54	
36-40	38	36	1368	12.41	37.59	2404.137	
41-45	43	37	1591	12.76	50.35	372.2786	50 th
46-50	48	39	1872	13.45	63.80	130.32	
51-55	53	30	1590	10.34	74.14	1398.648	
56-60	58	22	1276	7.59	81.73	3077.835	85 th
61-65	63	21	1323	7.24	88.97	5946.813	
66-70	68	20	1360	6.90	95.87	9529.232	
71-75	73	7	511	2.41	98.28	5038.191	
76-80	78	5	390	1.72	100	5065.108	
Total		290	13360			56971.69	

The median speed is a middle volume speed in the distribution whole volume which is arranged in ascending order. It is also called 50th percentage speed (P50).

$$\begin{aligned}
 \text{Median} &= L + \frac{\frac{n}{2} - f_i}{f_m} \times C \\
 \text{Median} &= 41 + \frac{\frac{290}{2} - 144}{37} \times 5 \\
 \text{Median} &= 41 + \frac{1}{37} \times 5 \\
 \text{Median} &= 41 + 0.1351 \\
 \text{Median} &= 41.1351 \text{ Km/hr}
 \end{aligned}$$

Standard deviation of rates is a proportion of the spread of the individual rates. Accepting an ordinary dispersion, the mean I in addition to and short one standard deviation contains around 68% of the vehicles, in addition to and less two standard deviations contains 95%, and in addition to and less three standard deviations contains 99.8%. The standard deviation of the example is processed by first computing the change of the example and after that accepting the square root as pursues:

$$s = \sqrt{\frac{\sum F_i \times (v_i - \bar{v})^2}{\sum F_i - 1}}$$

$$s = \sqrt{\frac{56971.69}{289}}$$

$$s = \sqrt{197.133}$$

$$s = 14.04 \text{ Km/hr}$$

Where: s = standard deviation of the distribution

$\sum F_i \times (v_i - \bar{v})$ = sum of the mean square frequencies.

$\sum F_i \times (v_i - \bar{v})^2$ = square of the sum of the mean frequencies.

The methods for various examples taken from a similar populace are disseminated ordinarily about the genuine mean of the populace with standard deviation of $s/\sqrt{n}$ where n is the standard deviation of the whole populace. In expansive examples ($n \geq 25$) the standard deviation of the example, s , is a decent gauge of the standard deviation of the populace. Hence:

The time mean speed is expressed a:

$$\bar{V}_t = \bar{V}_t + s$$

$$\bar{V}_t = 46.069 + 14.04$$

$$\bar{V}_t = 60.11 \text{ km/hr}$$

Passenger Car Unit (PCU) is a metric utilized in Transportation Engineering, to evaluate activity stream rate on a thruway. A Passenger Car Unit is a proportion of the effect that a method of transport has on activity factors, (for example, progress, speed, thickness) contrasted with a solitary standard traveler auto. This is otherwise called traveler auto proportional. For instance, ordinary estimations of PCU (or PCE) are: Highway limit is estimated in PCU/hour day by day.

Table 3
Flow in PCU 28-05-2018

Time	Flow in PCU
7:30 to 8:30	364.1
8:30 to 9:30	382.8
9:30 to 10:30	402.3
10:30 to 11:30	367.3
16:30 to 17:30	339.2
17:30 to 18:30	413.8
18:30 to 19:30	425.5
19:30 to 20:30	341
20:30 to 21:30	358.7
21:30 to 22:30	377.4

The initial phase in this arrangement is to locate the aggregate movement volume for every hour long period as far as traveler auto units. For this reason the PCU esteems given in the table are utilized. When we have this, we can find the hour with the most astounding volume and the hour long interim with the most astounding volume. The pinnacle hour is appeared in blue beneath with the pinnacle hour long period appeared in a darker shade of blue. The pinnacle hour volume is only the entirety of the volumes of the six hour long interims inside the pinnacle hour (2230.9 PCU). The pinnacle hour long volume is 425.5 PCU for this situation. The pinnacle hour factor (PHF) is found by isolating the

pinnacle hour volume by six times the pinnacle hour long volume.

The genuine (outline) stream rate can be ascertained by separating the pinnacle hour volume by the PHF, $2230.9/0.8738 = 2553.10$ PCU/hr,

Similarly the above data's are taken from 29-05-2018 to 31 -05-2018




Fig 9 Cumulative frequency variations of classified vehicles at different speed class on different days.




Fig 10 Observed frequency variations of classified vehicles at different speed class on different days.




Fig 11: Flow in PCU on different days.

V. CONCLUSIONS

1. Combination at Bus and Truck Bays: Near Shubham Automobile, the transports and trucks are stopped out and about making an issue to different vehicles passing the crossing point.

Arrangement: While going from Shubham Automobile to Hero Motocorp at Vidisha the transports stop out and about because of absence of transport inlet space so a transport narrows can be give after the flag. The Bus driver ought to be told to not to stop the transports out and about and mindfulness might be made among the general population not to look

out for the street for transports and to utilize transport narrows. The transport cove close more (Hero Motocorp) is by and by not being used. The transport inlet must be remodelled by laying another street so it very well may be viably utilized.

2. Convergence of activity stream: Near Shubham Automobile gigantic volume of movement is utilizing left turn or Right turn and in the process lion's share of street is obstructed on either side. It is prescribed to give a flag and a free left with the goal that the activity stream inverse way isn't impeded.

3. The most extreme speed out and about is equivalent to 70-85. The drivers nearly don't surpass this speed. It was validated by our investigation where the vehicles were moved with the scope of speed from 30 to 55 km/hr

4. Amid 18:30-19:30 hour the quantity of vehicle passed perception point is 364 that likewise is equivalent to 425.5 PCU.

5. The most showing up sort of vehicles is the bike which is (145 bikes/hour).

6. This specific region contains billboards about speed point of confinement of 30km/hr and a portion of the drivers over surpass as far as possible (km/h). So it ought to be guaranteed that drivers don't separation speed constrain.

REFERENCES

- [1] Khanna, S.K., and Justo, C.E.G., (1993), "Thruway Engineering", New Chand and Bros, seventh Edition, New Delhi.
- [2] Nicholas J. Garber, Lester A. Hoel, (2009) , " Traffic and Highway designing " , fifth version , U.S.A.
- [3] ITE, Brian Wolshon, Anurag Pande (2016) , " Traffic building handbook " , seventh release , New Jersey.
- [4] Thomas R. Currin (2012) "Prologue to activity designing", second release. U.S.A
- [5] Dr. L.R. Kadiyali, "Movement Engineering and transport arranging" , ninth version , New Delhi.
- [6] F D Hobbs. , (1979), " Traffic arranging and building", second version.
- [7] Theodore M Matson, Wilbure S smith, fedric W Hurd, (1955)
- [8] Arash Moradkhani Roshandeh , Mahmood Mahmoodi Nesheli, and Othman Che Puan , " evalutation of movement attributes a contextual investigation " International Journal of Recent Trends in Engineering, Vol. 1, No. 6, May 2009.
- [9] Section 166 of the Transport Operations (Road Use Management) Act 1995.
- [10] S K Khanna (2010), Traffic Engineering, Highway Engineering, Nem Chand and Bros.
- [11] AASHTO. 2001. A Policy on Geometric Design of Highways and Streets (Green Book). fourth ed. Washington, D.C.: American Association of State Highway and Transportation Officials.
- [12] Capelle, D. G., Clevelend, D. E. what's more, Rankin, W. W. An Introduction to Highway Transportation Engineering, Institute of Traffic Engineers, USB.
- [13] Indian Road Congress, Recommendations with respect to Alignment, review and Geometric outlines, IRC: 52-1981.
- [14] Drew, D.R., Traffic stream hypothesis and control, McGraw-Hill Book Co., New York.
- [15] Kennedy, N., Kell, J. H. what's more, Homburger W. S., Fundamentals of Traffic Engineering, Institute of Transportation and Traffic Engg., University of California.
- [16] Roger P. Roess, Elena S. Prassasand William R. McShane, TRAFFIC ENGINEERING 3rdEdition, Pearson Education International, 2004.
- [17] Saito, M., Merkley, M. C., and Smith, P. "Instruments and Techniques for Mitigating Queues at Work Zones." Utah Department of Transportation Report No. UT-08.30, Department of Civil and Environmental Engineering, Brigham Young University, Provo, Utah, 2008.